



PRODUCTION INSTRUCTION OF PO - 1813 / AO-AZ-2 / CLAY 15855 - SHAGGY BORDER

DESCRIPTION	50*80	60*100	70*130
Party Quality	1800	1800	1800
Party Weight	0.72	1.080	1.637
Production Quality	1873	1750	1748
Production Weight	0.75	1.025-1.050	1.555-1.590
Pile Height - A	41-42 MM	41-42 MM	41-42 MM
Pile Height - B	22-23	22-23	22-23
Pile Height - C	0	0	0
Stitching 10 Cm A	18-19	18-19	18-19
Stitching 10 Cm B	12-13	12-13	12-13
Stitching 10 Cm C	0	0	0
Width in Line 5 cms	11 LINE	11 LINE	11 LINE
Middle Gape / Weaving Com	CAM GAPE	CAM GAPE	CAM GAPE
1. Yarn UV/Non UV	UVC	UVC	UVC
2. Canvas UV/Non UV	CANVAS 64 .600 GSM	CANVAS 53 .600 GSM	CANVAS 59 .600 GSM
3. Canvas Size	64'	53'	59'
4. Canvas Quality	.600 GSM	.600 GSM	.600 GSM
5. Canvas Weight @ PC.	.280	.380	.587
6. Canvas Cutting Size	53*88	63*110	73*142
7. Piben Tanki Fold	AS PER SAMPLE	AS PER SAMPLE	AS PER SAMPLE
8. Stiching in 5 CMS	8-9 TANKE	8-9 TANKE	8-9 TANKE
9. Piben Folder MM	38 MM	38 MM	38 MM
10. Latex	YES	YES	YES
11. Export Packing	YES	YES	YES

12. Carving	NO	NO	NO
TUMBLER / WASHING	0	0	0
PC DYEING WEIGHT	.725	1.037	1.572
PC WASHING WEIGHT	0	0	0
TUMBLING WEIGHT	0	0	0
TUFFTING FINAL WEIGHT	.700-.750	1.025-1.050	1.555-1.590
EXTRA WORK WEIGHT	0	0	0
ORDER QUANTITY	418	410	400